

# Belt Dressing Spray



## Safety and health

When using products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets must be observed.

### suitable for highly-stressed power-transmission belts

Belt Dressing Spray is a transparent belt coating based on synthetic elastomers for the most diverse types of heavily stressed drive belts.

It increases the service life, prolongs the durability of machines and systems, prevents belt slip, transmits the full drive capacity, eliminates and prevents squeaking, penetrates deep into pores, increases the effectiveness of the tensile strength, increases friction and promotes adhesion, prevents static charging, ensures suppleness and protects against ageing.

Belt Dressing Spray is suitable for many different types of belts made from all common materials such as fabric, leather, rubber or PVC. It can be used for V-belts, link belts, drive belts, flat belts, round belts, toothed belts, transmission belts, ribbed belts or conveyor belts.

Belt Dressing Spray is particularly suited for all types of drive belts in machines, aggregates, compressors, pumps, generators, conveyors, mills, pillar drills, and cooling units. The product can be used in many industrial sectors.

### Technical Data

Odour	mineral oil
Storage stability	24 months
Colour	colourless
Temperature resistance	-40 to +80 °C

### Processing

Spray in sufficient quantity onto the part to be treated and allow to react. If necessary, wipe off with a clean cloth. Repeat process as required. Avoid contact with plastic and varnished surfaces.

### Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

## Technotopogs FZCO

Head Office Middle East: Hamriya Free Zone-Sharjah, UAE  
 Tel: +971 6 5262004 • Fax: +971 6 5262030  
 info@technotopogs.com • www.technotopogs.com

Westhafenplatz 1  
 60327 Frankfurt/Main, Germany  
 Tel: +49 (0) 69 710456072