

Silicone-Fluid



special sliding and lubricating agent for sensitive areas

Silicone-Fluid is a special, physiologically harmless sliding agent and lubricant for sensitive areas. Silicone-Fluid can be used as release-, protective- and care agent on the most different surfaces like plastics, metal, stainless steel and rubber.

Silicone-Fluid has a durable and good surface quality and is temperature-resistant up to +250°C (+482°F). Due to its special formula and the resulting NSF H1 approval, Silicone-Fluid is used to improve workplace safety and health protection.

Technical Data

Odour	odourless
Features	NSF H1 approval
Storage stability	24 months
Colour	colourless
Temperature resistance	-30 to +250 °C

Processing

Clean and degrease surfaces before processing. Shake well the aerosol can and spray with a distance of approx. 25 cm. Do not apply this aerosol during production or transport processes of foods.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Safety and health

When using products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets must be observed.

Technotopogs FZCO

Head Office Middle East: Hamriya Free Zone-Sharjah, UAE
 Tel: +971 6 5262004 • Fax: +971 6 5262030
 info@technotopogs.com • www.technotopogs.com

Westhafenplatz 1
 60327 Frankfurt/Main, Germany
 Tel: +49 (0) 69 710456072