

Silicone Spray



sliding and release agent

Silicone Spray is a sliding and release agent as well as a preservative and care product for plastic, rubber and metal.

Silicone Spray provides a durable separating film and good surface properties.

Silicone Spray prevents the formation of adhesive residues on presses and guides, prevents products from sticking to conveyor belts, chutes and sliding ways, protects electrical contacts from moisture, preserves rubber, plastic and metal parts, protects rubber parts from becoming brittle, freezing and sticking and allows sunroof rails, seat tracks and seatbelt to run smoothly.

Technical Data

Odour	solvent
Features	silicone oil basis
Storage stability	24 months
Colour	colourless
Temperature resistance	-50 to +250 °C

Processing

Clean and degrease surfaces to be treated. Shake can and spray at about 25 cm from surface.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Safety and health

When using products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets must be observed.

Technotopogs FZCO

Head Office Middle East: Hamriya Free Zone-Sharjah, UAE
Tel: +971 6 5262004 • Fax: +971 6 5262030
info@technotopogs.com • www.technotopogs.com

Westhafenplatz 1
60327 Frankfurt/Main, Germany
Tel: +49 (0) 69 710456072